



ENTRY STATION

Entry Station With 2D Barcode Printed Ticket From Roll

Parqube LE is a flexible unit that fully controls lane entry by issuing a barcoded ticket to all transient users, by checking card, TAG, etc. to all permanent users. Full color graphic display option, gives clear user messages. Double language display capability. Manages all languages.

Parking
technology

HUB



Base model

- Outdoor housing
- Lockable access doors on two sides
- Structure made of extruded aluminum
- Two extruded aluminum doors painted RAL 7021
- Front/rear aluminum made sheets painted RAL 9003
- Intercom button & cover
- Backlit push button for ticket request
- 2D thermal printer unit with cutter
- Ticket cut from thermal paper roll
- Electronic control board for communication with central unit by RS485 network or TCP/IP
- 270mm roll thermal paper for 9000 (80gr) or 4500 (140gr) tickets
- Heater & fan with built-in thermostat

Options

- ParQube style wrapping film for front side on standard color casing
- Customized ParQube style wrapping film
- Customized color housing
- Passive proximity reader for cards 125 kHz ISO size
- Active or passive AVI readers
- Backlit LCD display 4 x 20 characters
- 7" LCD screen
- Analog intercom system
- Intercom over IP
- Fan fold thermal paper ticket

Standard Features

- Online with central unit
- RS485 communication network as standard or TCP/IP by ETH converter
- High resolution printer-200 DPI (8 dots/mm)
- Up to 5.000 users storage offline
- Up to 15.000 events storage offline
- Free input for external reader
- Passive proximity reader for cards 125 kHz ISO size
- Active or passive long range reader (AVI managed by software)
- Antipassback card management online with central unit
- Opening pulse operating against valid ticket or card check
- Function setting by an on board jumper



Peripheral Dimensions (W x D x H)

425 mm x 360 mm x 1262 mm

16.7 x 14.1 x 49.7

Power Consumption

225w

Electrical

100-120 / 220-240 V ~ 50-60 Hz

Temperature

-20°C / + 50°C