

6000HD-19 Automatic Barrier

Part of the **6000 BARRIER RANGE**

DESCRIPTION



PLUG & PLAY
INSTALLATION

Skirts | Hi-Bars | LEDs | Sensors | Plug & Play


- 100% duty cycle heavy industrial usage
- Designed to be safe yet secure
- Single Phase Supply
- Plug & Play installation
- Programmable control panel c/w fault diagnostic on screen display
- Highest specification of components are ONLY used
- Integrates with other devices to make a secure perimeter
- Aluminium construction for long lasting/maintenance free performance
- Dual safety control for vehicles so making safe and reliable
- A VERY easy to use manual release mechanism which requires no tools in the event of power failure.

6000 ADDED BENEFITS

- Ease of installation
- Low maintenance
- 99.9% Access Control compat
- Safe trusted program logic
- Accepts 2 8k2 CAT3 safety
- Designed and built to last
- Effective security deterrent

OPTIONAL EXTRAS

- LED Traffic lights
- Articulated Arm
- Bottom Skirt/Hi-Bar Skirting
- Warning Signage
- Pogo Tip Support



"INDUSTRY STANDARD"

Our barriers have been classed as the best in the industry. It has been designed to last using the best materials and components that we can buy. As with all our products they are 100% Duty Cycle

THE UK'S No.1 TRIED, TESTED & TRUSTED AUTOMATIC BARRIERS

Our designs use the latest technology to maintain the barriers smooth operation, via an integral frequency inverter driven motor and gearbox drive, which only requires a single phase supply, providing a smooth consistent operation.

It is controlled by a Feig Control Board, which can be programmed to suit any site configuration & form of access control requirements, therefore allowing speedy installation and no return visits to modify the programmes.

The power input to our automatic barrier is 230v controlling a three phase motor, hence enables us to offer reliability and high torque. With this control panel and gearbox design, we do not require any springs or counterweights to assist in the operation of the barriers.

Our aluminium externally placed control cabinet has been designed to stand out from the rest. Its sleek looks are achieved by investing heavily into aluminium extrusions, which ensures product longevity, making it look as good as the day it was installed.



ABSOLUTE CONTROL

The 6000 auto barriers feature a Feig control panel that is far more advanced for safety and motion than its rivals

6000HD-19 Automatic Barrier



PRODUCT SPECIFICATION

Operation Speed

8 to 22 Seconds
 (Speed WILL vary dependant upon barrier configuration)

Duty Cycle

100% Heavy Industrial Usage

Specification

CE Approved, TUV Approved

Power Requirements

Single Phase 240v 50Hz 10 Amps

Maximum Span Dimensions

9M plain pole only | 8M with bottom skirt | 6.5M with hi-bar

Drive Unit

3 Phase Motor & Wormed Gearbox

Material Construction

Aluminium & Polyester Powder Coated

Ambient Temperature

-20°C to +60°C (+65°C with vent kit (charges apply))

Unit Weight

Cabinet, contents and pole arm: 102Kg

Dimensions

Cabinet: 1120mm x 455mm x 490mm

Pole: 123mm x 84mm OVAL

IP Rating

Ip56

Fixings


M16 anchor shield bolts included



PLUG & PLAY
INSTALLATION

Bright LED
Red/Green Lights
(Additional Cost)

Aluminium Lid & Body
Long Lasting Corrosion
Free




Integrated 8K2
Safety Edge as STD



Beautifully Designed
Strong Secure Cabinet

Bottom Skirt &
Hi-Bar Skirt Options



COLOURS

Red with white lid, and yellow with black lid, colours are standard with monitored safety edge. Custom cabinet colours are possible at extra cost.

CAD Drawings
provided as
standard



Tech Support
provided and
FREE mobile
APP as
standard

