

# ParQube LX

## **Base model**

- Outdoor housing
- Lockable access doors on two sides
- Structure made of extruded aluminum
- Two extruded aluminum doors painted RAL 7021
- Front/rear aluminum made sheets painted RAL 9003
- Intercom button & cover
- Omni-directional laser scanner for tickets
- Electronic control board for communication with central unit by RS485 network or TCP/IP
- Heater & fan with built-in thermostat

# **Options**

- ParQube style wrapping film for front side on standard color casing
- Customized ParQube style wrapping film
- Customized color housing
- Passive proximity reader for cards 125 kHz ISO size
- Active or passive AVI readers
- Backlit LCD display 4 x 20 characters
- 7" LCD screen
- Analog intercom system
- Intercom over IP
- Fan fold thermal paper ticket
- Automated exit by plate recognition (LPR) for paid tickets

# **Standard Features**

- Online with central unit
- RS485 communication network a standard or TCP/IP by ETH converter
- Up to 5.000 users storage offline
- Up to 15.000 events storage offline
- Free input for external reader
- Two way barcode ticket scanning
- Passive proximity reader for cards 125 kHz ISO size
- Active or passive long range reader (AVI managed by software)
- Antipassback card management online with central unit
- Opening pulse operating against valid ticket or card check
- Function setting by an on board jumper



#### Peripheral Dimensions (W x D x H)

425 mm x 360 mm x 1262 mm 16.7 x 14.1 x 49.7

#### **Power Consumption**

225w

### Electrical

100-120 / 220-240 V ~ 50-60 Hz

#### **Temperature**

-20°C / + 50°C



